



Red Hat Enterprise Linux 7 Getting Started with Cockpit

Getting Started with Cockpit

Red Hat Enterprise Linux Documentation
Team

Getting Started with Cockpit

Legal Notice

Copyright © 2017 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux ® is the registered trademark of Linus Torvalds in the United States and other countries.

Java ® is a registered trademark of Oracle and/or its affiliates.

XFS ® is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL ® is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js ® is an official trademark of Joyent. Red Hat Software Collections is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack ® Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

This guide demonstrates how to use the Cockpit web-based interface to manage Red Hat Enterprise Linux and Red Hat Enterprise Linux Atomic Host servers.

Table of Contents

CHAPTER 1. OVERVIEW	3
1.1. WHAT MAKES COCKPIT UNIQUE?	3
1.2. THE ROLE OF THIS GUIDE	3
CHAPTER 2. INSTALLING AND ENABLING COCKPIT	4
2.1. PREREQUISITES FOR A COCKPIT SERVER	4
2.2. SETTING UP THE PRIMARY COCKPIT SERVER	4
2.3. OPENING THE INTERFACE	5
2.4. CHANGING EXPIRED PASSWORDS	5
2.5. SSH TWO-FACTOR AUTHENTICATION WITH COCKPIT	7
CHAPTER 3. USING COCKPIT	8
3.1. GETTING TO KNOW THE COCKPIT INTERFACE	8
3.1.1. Adding secondary systems	16
3.1.2. Logging into other systems through Cockpit	18
3.1.3. Logging into a system via a Bastion Host	19
3.2. CHANGING THE COCKPIT PORT	19
3.3. ENABLING MORE COCKPIT FEATURES	20
CHAPTER 4. COCKPIT ON RED HAT ENTERPRISE LINUX ATOMIC HOST	21
4.1. INSTALLING COCKPIT ON ATOMIC HOST	21
4.2. COCKPIT INTERFACE SPECIFIC TO ATOMIC HOST	21
4.2.1. Working with Containers	23
4.3. CHANGING THE COCKPIT PORT ON ATOMIC HOST	27
4.4. ENABLING MORE COCKPIT FEATURES ON ATOMIC HOST	27

[Click here to download full PDF material](#)